



KONICA MINOLTA

bizhub c257i

Colour A3 multifunctional

**bizhub
i-SERIES IS
SMARTER
WORKING**
RETHINK IT



Giving Shape to Ideas

CUSTOMER BENEFITS



Intuitive operability
Operate the bizhub like a smartphone or tablet with fully customised user interface



Mobile connectivity
Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security
Secure network integration, data encryption, hard drive overwrite, and advanced user authentication



Application ecosystem
Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Services
Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup



Sustainability
Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS

1 ENHANCED FEATURES

- PDF enhancements
LK-102v3
- OCR text recognition
LK-105v4
- Barcode fonts
LK-106
- Unicode fonts
LK-107
- OCR A and B fonts
LK-108
- Document converter pack
LK-110v2
- ThinPrint® client
LK-111
- Serverless pull printing
LK-114
- Trusted Platform Module activation
LK-115v2
- Antivirus
LK-116
- FOIP activation
LK-117



2 CONNECTIVITY

- Fax board
FK-513
- Wireless LAN
UK-221
- USB I/F kit
EK-608
- USB I/F kit
EK-609
- Biometric authentication
AU-102
- ID card reader
- Mount kit
MK-735

3 OTHERS

- Document feeder
DF-633
- Original cover
OC-513
- Working table
WT-515
- 10-Key pad
KP-101
- Air cleaning unit
CU-101
- Mount kit
MK-748

4 MEDIA INPUT

- 1 x Universal tray
PC-118
- 2 x Universal tray
PC-218
- Large capacity tray
PC-418
- Copier desk
DK-518x
- Banner tray
BT-C1e

5 MEDIA OUTPUT

- Job Separator
JS-506
- Attachment kit
MK-603
- Inner Finisher
FS-533
- Attachment kit
MK-603
- Attachment kit
MK-602
- Punch kit
PK-519
- Staple finisher
FS-539
- Attachment kit
MK-603
- Relay unit
RU-514
- Staple/booklet finisher
FS-539SD
- Attachment kit
MK-603
- Relay unit
RU-514
- Punch kit
PK-524

LEGEND

- Mandatory option
- Option
- This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES



Corner stapling



Two-point stapling



Two-hole punching



Four-hole punching



Duplex



Combined mixplex/mixmedia



Half-fold



Sheet insertion, report



Letter-fold



Booklet



Offset sorting



Banner printing



Corner Stapling (offline)

DESCRIPTION

ENHANCED FEATURES

| | |
|----------------------------------|--------------------------------------------------------------------------------------|
| LK-102v3 PDF enhancements | PDF/A(1b), PDF encryption, digital signature |
| LK-105v4 OCR text recognition | Searchable PDF and PPTX |
| LK-106 Barcode fonts | Supports native barcode printing |
| LK-107 Unicode fonts | Supports native Unicode printing |
| LK-108 OCR A and B fonts | Supports native OCR A and B font printing |
| LK-110v2 Document converter pack | Generates various file formats incl. DOCX, XLSX and PDF/A |
| LK-111 ThinPrint® client | Print data compression for reduced network impact |
| LK-114 Serverless pull printing | Secure and Follow Me printing solution requiring no server application. |
| LK-115v2 Trusted Platform Module | Trusted Platform Module for protection of data encryption and decryption |
| LK-116 Antivirus | Bitdefender® antivirus provides real time scanning of all incoming and outgoing data |
| LK-117 FOIP activation | Fax over IP networks (T.38), requires fax kit |

CONNECTIVITY

| | |
|---------------------------------|-------------------------------------------------|
| EK-608 USB I/F kit | USB keyboard connection |
| EK-609 USB I/F kit | USB keyboard connection; Bluetooth |
| UK-221 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| FK-513 Fax board | Super G3 fax, digital fax functionality |
| MK-735 Mount kit | Installation kit for ID card reader |
| AU-102 Biometric authentication | Finger vein scanner |

OTHERS

| | |
|--------------------------|-------------------------------------------------------------|
| DF-633 Document feeder | Reversing automatic document feeder, capacity 130 originals |
| OC-513 Original cover | Cover instead of ADF |
| WT-515 Working table | Working table for upright panel |
| KP-101 10-Key pad | For use instead of touchscreen |
| CU-101 Air cleaning unit | Improving indoor air quality by reduced emissions |
| MK-748 Mount kit | Installation kit for Air cleaning unit |

MEDIA INPUT

| | |
|----------------------------|------------------------------------------------------------|
| PC-118 Universal tray | 500 sheets, A5-A3 60-256 g/m ² |
| PC-218 Universal tray | 2x 500 sheets, A5-A3, 60-256 g/m ² |
| PC-418 Large capacity tray | 2,500 sheets, A4, 60-256 g/m ² |
| DK-518x Copier desk | Provides storage space for print media and other materials |

MEDIA OUTPUT

| | |
|--------------------------------|--------------------------------------------------------------------------|
| FS-533 Inner finisher | 50-sheet stapling, 500 sheets max. output |
| FS-539 Staple finisher | 50 sheets stapling; 3,200 sheets max. output |
| FS-539SD Booklet finisher | 50 sheets stapling; 20 sheets booklet finisher; 2,200 sheets max. output |
| MK-602 Attachment kit | For FS-533 installation |
| MK-603 Attachment kit | For FS-533, FS-539/SD, JS-506 installation |
| PK-524 Punch kit for FS-539/SD | 2/4 hole punching; autoswitching |
| JS-506 Job separator | Separation of fax output; etc. |
| PK-519 Punch kit for FS-533 | 2/4 hole punching, autoswitching |
| RU-514 Relay unit | For FS-539/SD installation |

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

| | |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| System speed A4 | Up to 25/25 ppm (mono/colour) |
| System speed A3 | Up to 12/12 ppm (mono/colour) |
| Autoduplex speed A4 | Up to 25/25 ppm (mono/colour) |
| 1st page out time A4 | 6.8/8.4 sec. (mono/colour) |
| Warm-up time | Approx. 20 sec. (mono/colour) ¹ |
| Imaging technology | Laser |
| Toner technology | Simitri® HD polymerised toner |
| Panel size/resolution | 7" / 800 x 480 |
| System memory | 6,144 MB (standard/max) |
| System hard drive | 256 GB SSD (standard) |
| Interface | 10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional) |
| Network protocols | TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour |
| Automatic document feeder (optional) | Up to 130 originals; A5-A3; 35-128 g/m ² ; RADF |
| Printable paper size | A6-A3; banner paper max. 1,200 x 297 mm |
| Printable paper weight | 60-256 g/m ² |
| Paper input capacity | 1,100 sheets /3,600 sheets (standard/max) |
| Paper tray input (standard) | 1x 500; A5-A4; custom sizes; 60-256 g/m ² 1x 500; A5-A3; custom sizes; 60-256 g/m ² |
| Paper tray input (optional) | 1x 500 sheets; A5-A3; 60-256 g/m ² 2x 500 sheets; A5-A3; 60-256 g/m ² 1x 2,500 sheets; A4; 60-256 g/m ² |
| Manual bypass | 100 sheets; A6-A3; custom sizes, banner; 60-256 g/m ² |
| Finishing modes (optional) | Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; Letter-fold; Booklet |
| Automatic duplexing | A5-A3; 60-256 g/m ² |
| Output capacity | Up to 250 sheets / up to 3,300 sheets (standard/max) |

SYSTEM SPECIFICATIONS

| | |
|------------------------------|----------------------------------------------------------------------------|
| Stapling | Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m ²) |
| Stapling output capacity | Max. 100 sets |
| Letter fold | Max. 3 sheets |
| Letter fold capacity | Max. 30 sets; unlimited (without tray) |
| Booklet | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m ²) |
| Booklet output capacity | Max. 20 booklets; unlimited (without tray) |
| Duty cycle (monthly) | Rec. 10,000 pages; Max. ² 125,000 pages |
| Toner lifetime | Black up to 24,000 pages CMY up to 24,000 pages |
| Power consumption | 220-240 V / 50/60 Hz; Less than 1.50 kW |
| System dimension (W x D x H) | 571 x 661 x 786 mm (without options) |
| System weight | Approx. 70.0 kg (without options) |

PRINTER SPECIFICATIONS

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Print resolution | 1,800 (equivalent) x 600 dpi |
| Page description language | PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS |
| Operating systems | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |
| Mobile printing | AirPrint (iOS); Mopria (Android); Konica Minolta Print Service (Android); Konica Minolta Mobile Print (iOS/Android) optional: WiFi Direct |

SCANNER SPECIFICATIONS

| | |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scan speed | Up to 55/55 ipm in simplex (mono/colour) |
| | Up to 20/20 ipm in duplex (mono/colour) |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan |
| File formats | JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX; PDF/A optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX |
| Scan destinations | 2,000 destinations + 100 groups; LDAP support |

COPIER SPECIFICATIONS

| | |
|-----------------|-------------------------------------|
| Copy resolution | 600 x 600 dpi |
| Gradation | 256 gradations |
| Multicopy | 1-9,999 |
| Original format | Max. A3 |
| Magnification | 25-400% in 0.1% steps; Auto-zooming |

FAX SPECIFICATION

| | |
|------------------|---------------------------------------|
| Fax standard | Super G3 (optional) |
| Fax transmission | Analogue; i-Fax; Colour i-Fax; IP-Fax |
| Fax resolution | Up to 600 x 600 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,000 single + 100 groups |

USER BOX SPECIFICATIONS

| | |
|----------------------|------------------------------------------------------------------------------------|
| Storable documents | Up to 3,000 documents or 10,000 pages |
| Type of user boxes | Public; Personal (with password or authentication); Group (with authentication) |
| Type of system boxes | Secure print; Encrypted PDF print; Fax receipt; Fax polling |

SYSTEM FEATURES

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Software | Net Care Device Manager; Data Administrator; Box Operator; Web Connection; Print Status Notifier; Driver Packaging Utility; Log Management Utility |
| Security Functions | ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network communi- cation; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive data encryption (AES 256); Confidential fax; Print user data encryption optional: Antivirus realtime scanning (Bitdefender®); Hard drive mirroring, Copy protection (Copy Guard, Password Copy) |
| Accounting | Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS) |

¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

